



Intake & Exhaust Fans Used with ArcticBlast Cooling

Typhoon Wall Exhaust Fan (21,000 cfm • 2 Speed)

Features / Specifications:

- Hot dipped after welded galvanized 1" x 2" wire mesh guards-removable.
- Optional pre-wired models available.
- Quiet operation.
- NEW plastic guard clips to reduce vibration for quieter performance.
- Cost efficient heavy duty 18 gauge galvanized housing construction for superior durability and longevity. Smooth spun venturi to maximize air flow dynamics.
- Galvanized deep cone to reduce back pressure and boost performance.
- Heavy duty galvanized X-frame motor mount provides solid motor mounting for increased motor life and quieter operation.
- Galvanized three blade props; highly efficient, easy cleaning, balanced for smooth operation and extended life of blade and motor.
- Cast aluminum 50" blades for high performance
- New available 50" 6 bladed propeller – features high performance / low noise.
- Totally enclosed, maintenance free, high efficiency motors have completely sealed all bearings.
- 2 Speed Motor: low cfm speed is 2/3 of high cfm.
- UL and ULC certification.
- Built in automatic thermal overload protection.
- Matched motor & belt ratio for maximum air, without overloading the motor.
- Belt drive 48" and 50" units are complete with heavy duty spring belt tensioner.
- Bearings are pre-lubricated, permanently sealed and rubber mounted to improve smooth operation & reduce blade fatigue. They also feature an eccentric locking double set screw collar.
- High performance aluminum shutters with tie bar to eliminate flapping.
- Available with single phase or 3 phase motors.
- **LIFETIME WARRANTY** on Cast Aluminum blades.
- US MADE. Full 2 year warranty.



Typhoon Exhaust Fan
Model # VNS50S2CA
50" • 21,000 cfm
1 hp • Belt Drive • 2 Speed
208-230/460 Volts
3.1-2.8/1.4 amps
550 RPM
3 Blade Cast Aluminum

Aluminum Intake Shutters

Features / Specifications:

- High efficiency shutter with tie bar to eliminate shutter flapping.
- Nylon bearings; solid shafts; drawn cup-type sleeves on all movable linkage.
- Frame of heavy aluminum extrusion with 1/2" channel lock water stop.
- Corners are precision milled – welded for durability.
- Interlocking blades for maximum weather seal
- Constructed with rigid "T" section center member.
- Optional motorized shutter kit available to turn any shutter into a power shutter
- US MADE. Full 2 year warranty

Aluminum Intake Shutter
Model # VRSG54A-C
54" x 54"
Double Panel

